


AP 300 EMX

AC MOTOR AIR-OIL HEAT EXCHANGERS
MARINE USE AND ATEX REGULATION EMX TYPE
SCAMBIATORI DI CALORE ARIA OLIO CON VENTILATORE A
CORRENTE ALTERNATA USO MARINO NORME ATEX SERIE EMX





- Dimensions and technical characteristics are not binding



Static working pressure = 20 bar

Test pressure = 35 bar

CODE	OIL FLOW	CAP.	VOLT.	FREQ.	POWER	CURRENT	AIR FLOW	PROT.	NOISE LEV.	WEIGHT	ø FAN	TEMP.
	l/min	l	V	Hz	W	A	m³/h	IP	dB(A)	kg	mm	°C
3RAP300EMX50	10-80	2	220-240(Δ) / 380-415 (Y)	50	180	0,75	1500	56	81	30	250	-20/+40
3RAP300EMX60	10-80	2	460 (Y)	60	285	0,6	1580	56	83	30	250	-20/+40



CORRECTION FACTOR							
cSt	22	30	46	68	100	150	220
f	0,6	1	1,5	2,3	3,5	5	7

PURCHASE CODES

AP 300 EMX three-phase 380-415V 50Hz	3RAP300EMX50
AP 300 EMX three-phase 460V 60HZ	3RAP300EMX60

SPARE PARTS

Cooling element	3RNL300A
Frame	3CNAP300EMX.1
Electric fan 380-415V 50Hz	1VNAP300EMX50
Electric fan 460V 60Hz	1VNAP300EMX60